



Part Number	Available Sizes	Ring Pack	Description	Compression Ratio				
AMC 401				50.6cc	56.5cc	58.0cc	58.6cc	
L2380NF	30, 40	5/64-5/64-3/16	.170" Dish	10.56	9.95	9.81	9.76	
BUICK 3.8L V6				48.0cc				
L2481F	Std, 30, 40	5/64-5/64-3/16	.245" Dish		7.96			
BUICK 455				66.0cc	68.0cc	69.0cc	71.0cc	77.5cc
L2353F	30, 40	5/64-5/64-3/16	.156" Dish	9.15	9.01	8.94	8.81	8.41
CHEVY 383				58.0cc	64.0cc	68.0cc	72.0cc	76.0cc
L2491NF	Std, 30, 40, 60	1/16-1/16-3/16	5.7" Rods, Flat Top, 2 valve reliefs	11.55	10.76	10.3	9.88	9.49
CHEVY 509				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
L2513F	Std, 30, 60	1/16-1/16-3/16	4.500" Bore, Flat Top		9.35	9.18	8.73	8.61
CHEVY 540				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
LW2634F	Std, 30	.043-.043-3.0mm	4.500" Bore x 4.250" Stroke, Lightweight, .450" Dome		14.41	14.01	12.96	12.69
LW2633F	Std, 30, 60	.043-.043-3.0mm	4.500" Bore x 4.250" Stroke, Lightweight, Flat Top, 2 valve reliefs		9.86	9.69	9.2	9.08
CHEVY 302				58.0cc	64.0cc	68.0cc	72.0cc	76.0cc
L2210AF	60	1/16-1/16-1/8	.410" Dome	13.41	12.2	11.52	10.91	10.38
L2210AF	30	1/16-1/16-1/8	.430" Dome	13.24	12.05	11.37	10.78	10.25
CHEVY 327				58.0cc	64.0cc	68.0cc	72.0cc	76.0cc
L2166NF	Std, 20, 30, 40, 60	5/64-5/64-3/16	.125" Dome	11.2	10.35	9.87	9.43	9.03
L2165F	Std, 20, 30, 40, 60	5/64-5/64-3/16	Flat Top, 4 valve reliefs	9.69	9.07	8.71	8.37	8.06
CHEVY 350				58.0cc	64.0cc	68.0cc	72.0cc	76.0cc
L2403NF	Std, 20, 30, 40, 60	5/64-5/64-3/16	.068 Dish	9.73	9.14	8.79	8.47	8.18
L2304F	Std, 30, 60	5/64-5/64-3/16	.100 Dome	11.4	10.63	10.15	9.71	9.31
LW2304F	40	1/16-1/16-3/16	Lightweight, .100 Dome	11.4	10.63	10.15	9.71	9.31
LW2626F	30, 40, 60	1.5-1.5-3.0mm	6.00" Rod, Lightweight, .100 Dome	11.46	10.63	10.15	9.71	9.31
L2252YF	30, 40, 60	1/16-1/16-1/8	.200 Dome	12.94	11.87	11.26	10.71	10.22
8LW2503F	30, 40, 60	1/16-1/16-3/16	Lightweight, 350 Dome		12.07	11.43	10.87	10.36
8LW2509F	30, 60	1/16-1/16-3/16	6.000" rod, Lightweight, .350 Dome		12.07	11.43	10.87	10.36
LW2603F	30, 60	1/16-1/16-3/16	Lightweight, 10.9cc Reverse Dome	9.53	8.97	8.63	8.32	8.04
L2441F	Std, 30	5/64-5/64-3/16	Supercharged or Turbo, 21.1cc D Cup	8.82	8.35	8.06	7.8	7.55
L2490NF	Std, 30, 60	1/16-1/16-3/16	2 valve reliefs	10.79	10.06	9.63	9.24	8.88
8LW2505F	30, 60	1/16-1/16-3/16	Lightweight, Flat Top, 2 valve reliefs	10.3	9.47	9.09	8.75	8.43
8LW2511F	60	1/16-1/16-3/16	6.000" rod, Lightweight, Flat Top, 2 valve reliefs	10.1	9.47	9.09	8.75	8.43
L2256F	Std, 20, 30, 40, 60	5/64-5/64-3/16	Flat Top, 4 valve reliefs	10.4	9.72	9.32	8.96	8.62
LW2256F	30, 40, 60	1/16-1/16-3/16	Lightweight, Flat Top, 4 valve reliefs	10.4	9.72	9.32	8.96	8.62
CHEVY 396				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
L2240NF	Std, 30, 40, 60	5/64-5/64-3/16	65-69, 325/350HP, .182 Dome		9.09	8.89	8.36	5.23
L2242NF	30, 40, 60	5/64-5/64-3/16	65-69, 375HP, .319 Dome			1.58	9.9	9.7
CHEVY 400				58.0cc	64.0cc	68.0cc	72.0cc	76.0cc
L2352F	30, 40, 60	5/64-5/64-3/16	.038 Dish	10.53	9.91	9.55	9.21	8.9
LW2606F	60	1/16-1/16-3/16	Lightweight, 16.2cc Reverse Dome	10.38	9.78	9.43	9.1	8.8
LW2629F	40, 60	1.5-1.5-3.0mm	6.00" Rod, Lightweight, 16.2cc Reverse Dome	10.39	9.79	9.44	9.11	8.81
LW2632F	30, 40, 60	1.5-1.5-3.0mm	5.70" Rod, Lightweight, 25cc Reverse Dome	9.54	9.05	8.75	8.47	8.21
L2489F	40	5/64-5/64-3/16	5.7" Rods, Flat Top, 2 valve reliefs	11.81	11.03	10.57	10.15	9.76
8LW2517F	30	1/16-1/16-3/16	5.700" rod, Lightweight, Flat Top, 2 valve reliefs	11.8	11.02	10.56	10.14	9.76
8LW2515F	30	1/16-1/16-3/16	5.700" rod, Lightweight, .150 Dome	13.6	12.55	11.94	11.4	10.9
CHEVY 402				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
L2383F	30, 40, 60	5/64-5/64-3/16	70-72, 350HP, .110 Dome	9.29	8.83	8.65	8.16	8.03
L2328NF	30, 60	5/64-5/64-3/16	.319 Dome		10.81	10.53		
CHEVY 427				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
L2300NF	Std, 30, 40, 60	5/64-5/64-3/16	66-69, 335/390HP, .140 Dome	9.98	9.46	9.27	8.73	8.59
L2268NF	30, 60	5/64-5/64-3/16	66-69, 425/435HP, .255 Dome		11.25		10.18	9.99
L2308AF	30, 60	1/16-1/16-3/16	.585 Dome				11.66	11.39
CHEVY 454				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
L2399NF	Std, 30, 40, 60	5/64-5/64-3/16	1971, LS-6, .095 Dome	10.23	9.71	9.52	8.98	8.84
L2349F	60	5/64-5/64-3/16	.210 Dome	11.84	11.15	10.89	10.18	10
L2349F	30	5/64-5/64-3/16	.221 Dome	11.89	11.18	10.91	10.19	10.01
L2349F	Std	5/64-5/64-3/16	.265 Dome	11.9	11.18	10.91	10.18	9.99
L2465F	60	1/16-1/16-3/16	.215 Dome	11.29	10.67	10.43	9.78	9.61
L2465F	30	1/16-1/16-3/16	.226 Dome	11.31	10.68	10.44	9.78	9.61
L2465F	Std	1/16-1/16-3/16	.270 Dome	11.34	10.69	10.44	9.78	9.6





Part Number	Available Sizes	Ring Pack	Description	Compression Ratio				
				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
CHEVY 454 (CONTINUED)				100.9cc	106.9cc	109.4cc	116.9cc	119.0cc
L2307AF	Std, 30, 60	1/16-1/16-3/16	.580 Dome				12.5	12.21
L2453F	Std, 30, 60	5/64-5/64-3/16	Supercharged or Turbo, 7.96cc D Cup	8.54	8.19	8.06	7.68	7.58
L2377F	Std, 20, 30, 40, 60	5/64-5/64-3/16	Flat Top, 2 valve reliefs	8.72	8.36	8.22	7.83	7.73
CHEVY 8.1L (496)								
L2641F	30, 40, 60	2.0-2.0-4.0mm	Flat Top, 2 valve reliefs					
CHEVY CORVAIR 164								
L2206F	Std, 20, 30, 40, 60	1/16-1/16-1/8						
CHEVY LS-1, 382 STROKER						66.0cc		
LW2624F	Std, 25MM	1.5-1.5-3.0mm	4.00" Stroker, 6.125" Rod, .927" pin, Flat Top, 2 valve reliefs			10.84		
CHEVY LS-1, 402 STROKER						66.0cc		
LW2625F	Std, 30, 60	1.5-1.5-3.0mm	4.00" Bore x 4.00" Stroke, 6.125" Rod, .927" pin, Flat Top, 2 valve reliefs			11.38		
CHEVY LS-1						66.0cc		
L2640F	30, 40, 60	1.5-1.5-3.0mm	4.000" Bore x 3.620" Stroke, .944" pin, Flat Top, 2 valve reliefs			10.04		
CHRYSLER 340					63.0cc	65.0cc	68.4cc	71.0cc
L2316F	20, 30, 40, 60	5/64-5/64-3/16	Flat Top, 2 valve reliefs		10.35	10.11	9.73	9.46
CHRYSLER 383						78.5cc	88.0cc	
L2315NF	30, 40, 60	5/64-5/64-3/16	Flat Top			9.77	8.94	
CHRYSLER 440						78.5cc	88.0cc	
L2295F	60	1/16-1/16-3/16	.125 Dome			11.34	10.34	
L2295F	30	1/16-1/16-3/16	.140 Dome			11.34	10.34	
L2266F	Std, 30, 40, 60	5/64-5/64-3/16	Flat Top			9.33	8.66	
L2355F	Std, 30, 40, 60	5/64-5/64-3/16	70-72, Six Pack, , 4 valve reliefs			10.17	9.37	
FORD 289/302				54.5cc	58.2cc	60.4cc	63.0cc	69.0cc
L2482F	Std, 20, 30, 40, 60	5/64-5/64-3/16	Flat Top, 4 valve reliefs	10.14	9.67	9.42	9.13	8.55
L2488F	Std, 20, 30, 40, 60	1.5-1.5-4.0mm	Flat Top, 4 valve reliefs	10.65	10.13	9.85	9.53	8.89
LW2488F	40	1/16-1/16-3/16	Lightweight, Flat Top, 4 valve reliefs	10.65	10.13	9.85	9.53	8.89
FORD 351 CLEVELAND					58.6cc	63.0cc	67.0cc	76.2cc
L2379F	Std, 30, 40	5/64-5/64-3/16	Flat Top, 2 valve reliefs		10.76	10.22	9.78	8.9
FORD 351 WINDSOR						60.4cc	63.0cc	69.0cc
L2446F	Std, 30, 40	5/64-5/64-3/16	.110 Dish			9.3	9.06	8.56
FORD 390					67.1cc	68.0cc	71.0cc	74.0cc
L2291F	Std, 20, 30, 40, 60	5/64-3/32-3/16	Flat Top, 4 valve relief		10	9.91	9.62	9.36
FORD 4.6L					44.0cc	51.8cc	54.0cc	
L2609F	50MM	1.5-1.5-3.0mm	4 valve engines, .060 Dish			11.88	10.5	
L2608F	Std, 50MM, 75MM	1.5-1.5-3.0mm	2 valve engines, .150 Dish			10.51	9.44	
L2623F	Std, 50MM, 75MM	1.5-1.5-3.0mm	Cobra, 4 valve, Supercharged, 13.5cc Dish			9.87	8.93	8.7
FORD 428					67.1cc	68.0cc	71.0cc	74.0cc
L2303NF	Std, 30, 40, 60	5/64-5/64-3/16	Cobra Jet, .085 Dish			10.66	10.35	10.07
FORD 429				72.0cc	73.5cc	77.0cc	92.0cc	97.0cc
L2366F	Std, 30, 40	5/64-5/64-3/16	Flat Top	11.1	10.93	10.56	9.23	8.87
FORD 460								
L2404F	Std, 30, 40, 60	5/64-5/64-3/16	.180 Dish	9.37	9.26	9.02	8.12	7.86
L2443NF	30, 60	5/64-5/64-3/16	.332 Dome			12.49	10.73	10.26
LW2602NF	30, 60	5/64-5/64-3/16	Lightweight, Flat Top, 1 valve relief	11.49	11.34	10.98	9.7	9.34
FORD 5.4L					44.0cc	51.8cc		
L2622F	Std, 50MM, 75MM	1.5-1.5-3.0mm	Lightning, 2 valve, Supercharged, 20.5cc Dish			8.6	7.99	
OLDS 350				64.0cc	70.0cc	72.0cc	75.0cc	80.0cc
L2321F	30	5/64-5/64-3/16	.076 Dish	9.67	9.09	8.91	8.66	8.28
L2320F	Std, 30	5/64-5/64-3/16	68-70, w/Outside Air, W-31, Flat Top	10.31	9.64	9.44	9.16	8.73
OLDS 455				64.0cc	70.0cc	72.0cc	75.0cc	80.0cc
L2323F	Std, 30, 40, 60	5/64-5/64-3/16	.142 Dish	10.68	10.12	9.95	9.7	9.32
PONTIAC 400				72.0cc	87.0cc	96.0cc	111.0cc	114.0cc
L2279NF	60	1/16-1/16-1/8	.190 Dome	11.93	10.15	9.34	8.26	8.08
L2279NF	30	1/16-1/16-1/8	.225 Dome	11.94	10.14	9.31	8.23	8.05
L2262F	Std, 20, 30, 40, 60	5/64-5/64-3/16	Flat Top, 4 valve reliefs	9.94	8.7	8.11	7.3	7.16
PONTIAC 455				72.0cc	87.0cc	96.0cc	111.0cc	114.0cc
L2359NF	Std, 30, 40, 60	5/64-5/64-3/16	Flat Top, 4 valve reliefs	11.51	10.01	9.3	8.34	8.17